

Roll No. 

--	--	--	--	--	--	--	--	--	--

Total No. of Pages : 02

Total No. of Questions : 09

B.Tech.(ME) (2011 Onwards) (Sem.-4)

**STRENGTH OF MATERIALS-II**

Subject Code : BTME-401

M.Code : 59129

Time : 3 Hrs.

Max. Marks : 60

**INSTRUCTION TO CANDIDATES :**

1. SECTION-A is COMPULSORY consisting of TEN questions carrying TWO marks each.
2. SECTION-B contains FIVE questions carrying FIVE marks each and students have to attempt ANY FOUR questions.
3. SECTION-C contains THREE questions carrying TEN marks each and students have to attempt ANY TWO questions.

**SECTION-A****1. Answer briefly :**

- a) What is energy of distortion?
- b) What is the necessity of theory of failure?
- c) Define stiffness of the spring.
- d) For what purposes cylindrical and spherical shells are used?
- e) State Lamé's equation.
- f) Which type of stresses are produced in a rotating thin disc of uniform thickness?
- g) What is meant by trapezoidal section?
- h) Where does the maximum vertical shear stress occur in an I-section?
- i) Discuss the importance of shear centre.
- j) Identify three principal stresses in a thick cylinder.



**SECTION-B**

2. Compare the strains produced in a body subjected to same amount of load when applied gradually and when suddenly.
3. A closed coil helical spring has mean diameter of 75 mm and spring constant of 80 kN/m. It has 8 coils. What is the suitable diameter of the spring wire if maximum shear stress is not to exceed  $250 \text{ MN/m}^2$ ? Modulus of rigidity of the spring wire material is  $80 \text{ GN/m}^2$ . What is maximum axial load the spring can carry?
4. For a thin cylindrical shell, the length/diameter ratio is 3 and its volume is  $20 \text{ m}^3$ . The safe tensile stress, for the shell material is 100 MPa. Determine the cylinder diameter and wall thickness if it is to contain water at an absolute pressure of 2 MPa.
5. Two closed coiled helical steel springs are connected in series to form a composite spring of stiffness 1.5 kN/m. In both the springs, mean coil radius is 4 times the wire diameter. One spring is made out of 3 mm diameter wire and has 20 turns, whereas the other spring has 15 turns. Determine the wire diameter in case of second spring.  $C = 80 \text{ GPa}$ .
6. Write a brief note on stress in rotating discs.

**SECTION-C**

7. A bar of mild steel carries an axial pull of 10 kN and a transverse shear force of 5 kN. Taking the elastic limit in tension as 240 MPa, a factor of safety 3 and Poisson's ratio 0.3, calculate the diameter of the bar if the criterion is (i) Maximum principle stress theory, (ii) Maximum strain energy theory.
8. A thick cylinder of 150 mm outside radius and 100 mm inside radius is subjected to an external pressure of  $30 \text{ MN/m}^2$  and internal pressure of  $60 \text{ MN/m}^2$ . Calculate the maximum shear stress in the material of the cylinder at the inner radius.
9. A beam 100 mm wide and 150 mm deep in cross-section is simply supported and carries a uniformly distributed load over its entire span of 2 m. If the allowable stresses for the beam material are 30 MPa in bending and 2 MPa in shear, calculate the maximum load which the beam can carry.

**NOTE : Disclosure of Identity by writing Mobile No. or Making of passing request on any page of Answer Sheet will lead to UMC against the Student.**