

www.FirstRanker.com

www.FirstRanker.com

Roll No.													Total No. of Pages: 0	2
----------	--	--	--	--	--	--	--	--	--	--	--	--	-----------------------	---

Total No. of Questions: 10

B.Pharma (2011 to 2016) (Sem.-4)
PHARMACEUTICS IV

(Unit Operation-II) Subject Code : BPHM-401 Paper ID : [D1140]

Time: 3 Hrs. Max. Marks: 80

INSTRUCTIONS TO CANDIDATES:

- SECTION-A is COMPULSORY consisting of FIFTEEN questions carrying TWO marks each.
- SECTION-B contains FIVE questions carrying FIVE marks each and students have to attempt any FOUR questions.
- SECTION-C contains FOUR questions carrying TEN marks each and students have to attempt any THREE questions.

SECTION-A

O1. Define:

- a. Mole fraction
- b. Size reduction
- c. Unit operations
- d. Viscosity
- e. Raoult's law
- f. Distillation
- g. Distillation
- h. CMC
- i. Heat transfer
- Volatility

1 M-46231 (S4)-32



Distinguish between:

- k. Freeze drying and vacuum drying
- positive deviation vs negative deviation from Raoult's law
- m. Ball mill and Hammer mill
- n. Single and multiple effect evaporators
- Colloidal mill and fluid energy mill.

SECTION-B

- Q2. A tube 0.09 in. OD is lagged with 0.02 in. layer of asbestose with a conductivity of 0.10 Btu/hr. ft² °F followed 0.06 in. layer of cork whose conductivity is 0.06 Btu/hr. ft² °F. If the temperature difference between inner and outer surface is 1400 °F, Calculate heat loss.
- Q3. Classify evaporators? What are the factors effecting evaporation.
- Q4. Explain the deviations from Raoult's law with examples.
- Highlight the mechanisms of drying. Brief principle of vacuum drying.
- Q6. Explain the principles of size Reduction.

SECTION-C

- Q7. Discuss the role of size separation in a size reduction process. Give principle and working of fluid energy mill.
- Explain the principle, construction and working of hammer mill.
- Q9. How could you calculate the number of theoretical plates needed for a distillation process?
- Q10. Comment on the following :
 - a. In spray drying, the temperature at which the sprayed droplet dries is much lower than the temperature of the gas used for drying.
 - Size reduction in ball mill is by impact only
 - Steam distillation occurs at 100°C.

NOTE: Disclosure of Identity by writing Mobile No. or Marking of passing request on any paper of Answer Sheet will lead to UMC against the Student.

2 | M-46231 (S4)-32

