

www.FirstRanker.com

www.FirstRanker.com

### Code: 15A01802

## B.Tech IV Year II Semester (R15) Advanced Supplementary Examinations July 2019 ADVANCED STRUCTURAL ENGINEERING

(Civil Engineering)

Time: 3 hours

Max. Marks: 70

# Answer all questions All questions carry equal marks

Design an interior panel of a flat slab with panel size 5 x 5 m supported by columns 4.5 m x 4.5 m. Provide suitable drop. Take live load as 4 kN/m<sup>2</sup>. Use M20 steel and Fe415 steel. Draw the reinforcement details by showing cross section at column strip.

#### OR

- 2 Design a chimney of height 60 m. Given external diameter 4.0 m, shell thickness 300 mm, wind intensity 1.9 kN/m<sup>2</sup>, thickness of fire brick lining – 100 mm, air Gap-100 mm, temperature difference - $80^{\circ}$ C, coefficient thermal expansion – 11 x  $10^{-6}/^{\circ}$ C, Es = 2.1 x  $10^{5}$  kN/mm<sup>2</sup>, unit weight of brick lined – 20 kN/m<sup>3</sup>. Use M25 concrete and Fe415 steel. Draw plan and sectional elevation.
- 3 Design a rectangular tank resting on ground with internal dimensions 7.0 x 5.5 x 2.75 m high. Take the free board as 300 mm. Use M25 grade concrete and HYSD steel of grade Fe415. Draw plan and sectional elevation.

### OR

<sup>4</sup> Design and detail the various elements of counter fort retaining wall to support difference in ground elevation of 9 m. The foundation depth may be taken as 1.5 m below ground level, with a safe bearing capacity of 160 kN/m<sup>2</sup>. Assume a level backfill with a unit weight of 16 kN/m<sup>3</sup> and an angle of shearing resistance of 30<sup>0</sup>. Assume a coefficient of friction,  $\mu = 0.5$ , between soil and concrete. Draw plan and sectional elevation.