

www.FirstRanker.com

www.FirstRanker.com

R15

Code: 15A56101

B.Tech I Year I Semester (R15) Supplementary Examinations June 2017

ENGINEERING PHYSICS

(Common to CE, EEE & CSE)

Time: 3 hours Max. Marks: 70

PART - A

(Compulsory Question)

Note: Physical constants: Planck's constant: $h = 6.63 \times 10^{-34}$ Js, Mass of the electron = 9.1×10^{-31} kg, Charge of the electron = 1.6×10^{-19} C Boltzmann's constant k_B = 1.38×10^{-27} JK⁻¹, Permeability of free space $\mu_0 = 4\pi \times 10^{-7}$ Hm⁻¹

- 1 Answer the following: (10 X 02 = 20 Marks)
 - (a) State working principle of semiconductor diode laser.
 - (b) What is diffraction? What is the impact of increasing number of slits on diffraction pattern?
 - (c) List different types of crystal systems.
 - (d) Draw the block diagram of non-destructive testing of specimen.
 - (e) Give two reasons to prove that the matter waves are not electromagnetic waves.
 - (f) Represent graphically the probability distribution of electrons in metal at T = 0 K and T > 0K.
 - (g) Draw the energy band diagram of extrinsic semiconductor and represent the position of Fermi level.
 - (h) What are the origins for the magnetic moment in an atom?
 - (i) What is Josephson effect? Write any two applications.
 - (j) How does top-down approach different from bottom-up approach?

PART - B

(Answer all five units, 5 X 10 = 50 Marks)

UNIT

2 Derive an expression for energy density of radiation in terms of Einstein's A & B coefficient for two level systems & obtain the condition for laser action.

OR

- 3 (a) What is fiber loss? Mention the factors for the fiber loss and explain them briefly.
 - (b) An optic glass fiber of refractive index 1.50 is to be clad with another glass to ensure total internal reflection that will contain light travelling within 5° of the fiber axis. What maximum index of refraction is allowed for the cladding?

UNIT - II

4 With neat diagram, explain the construction and working of Debye-Scherer method (powder method) and discuss how to determine interplanar spacing of the crystal.

OR

- 5 (a) What are ultrasonic waves? Mention their properties and applications.
 - (b) The results of the X-ray diffraction investigation shows that, for a given crystal, two successive orders of reflection maxima occurs at the glancing angle of 8°58^I and 12°1^I. Evaluate the order of reflection corresponding to the glancing angle of 18°12^I.

Contd. in page 2





www.FirstRanker.com

www.FirstRanker.com

R15

Code: 15A56101

UNIT - III

- 6 (a) Setup time-independent Schrodinger wave equation of a particle in motion.
 - (b) Calculate the wavelength associated with an electron subjected to a potential difference of 1.25 kV.

OR

- 7 (a) What is energy bond? Explain the formation of energy bond due to the interaction of atoms in sodium metal.
 - (b) Calculate the probability of an electron occupying an energy level 0.02 eV above the Fermi level at 200 K in a metal.

UNIT - IV

- 8 (a) What are hard and soft magnetic materials? Mention their properties based on hysteresis loop and mention the applications.
 - (b) Diamagnetic material Al₂O₃ is subjected to an external magnetic field of 10⁵ Am⁻¹. Evaluate magnetization and magnetic flux density in Al₂O₃. Given: Susceptibility of Al₂O₃ is 5 x 10⁵.

OR

- 9 (a) What is drift current? Derive an expression for drift current in case of semiconductor.
 - (b) A silicon plate of thickness 1 mm, breadth 10 mm and length 100 mm placed in magnetic field of 0.5 Wbm⁻² acting perpendicular to its thickness. If 10⁻²A current flows along its length, calculate hall voltage developed if the hall coefficient is 3.66 x 10⁻⁴ m³c⁻¹.

UNIT - V

- 10 (a) What is Meissner effect? Show that a superconductor behaves as diamagnetic material.
 - (b) The critical fields for sample are 1.4 x 10⁵ and 4.2 x 110⁵ Am⁻¹ at 14K & 13K respectively. Find the transition temperature of the sample.

OF

- 11 (a) What are nanomaterials? Find surface-to-volume ratio when 1 cm cubical object reduces to 1 mm cubical object. Mention its significance.
 - (b) Discuss how the synthesis of nanomaterials is done using ball mill technique.

