

(Following Paper ID and Roll No. to be filled in your Answer Books)

Paper ID : 100411

Roll No.

B.TECH.

Theory Examination (Semester-IV) 2015-16

HYDRAULICS & HYDRAULIC MACHINES

Time : 3 Hours

Max. Marks : 100

Section-A

Attempt all parts. All parts carry equal marks.

Q.1. Write answer of each part in short. (2×10=20)

- (a) Define open channel flow with example.
- (b) Describe specific energy?
- (c) State the relation between Manning's constant and Chezy's constant

(1)

P.T.O.

106/432/419/10475

- (g) Hydraulic jump is sometimes used as energy dissipator at the toe of the spillway of a dam. why?
- (h) What is meant by Cavitations?
- (i) Define celerity of the surge
- (j) Give the range of specific speed values of Kaplan. Francis turbine and peltonwheels.

**Section-B**

Q.2. Attempt any 5 questions from this section. (10×5=50)

- (a) Classify the following open-channel flow situations:
- (a) Flow from a sluice gate

(2)

- (c) Derive an expression for the discharge through a channel by Chezy's Formula.

- (d) The width of a horizontal rectangular channel is reduced from 3.5 m to 2.5 m and the floor is raised by 0.25 m in elevation at a given section. At the upstream section, the depth of flow is 2.0 m and the kinetic energy correction factor  $\alpha$  is 1.15. If the drop in the water surface elevation at the contraction is 0.20 m, calculate the discharge if (a) the energy loss is neglected, and (b) the energy loss is one-tenth of the upstream velocity head. [The kinetic energy correction factor at the contracted section may be assumed to be unity].

- (e) What is critical depth in open-channel flow? For a given average flow velocity, how is it determined?

(3)

P.T.O.

(i) Uniform Flow in a open channel

(ii) Reaction turbine

- (b) A spillway discharges a flood flow at a rate of  $7.75 \text{ m}^3/\text{s}$  per metre width. At the downstream horizontal apron the depth of flow was found to be  $0.50 \text{ m}$ . What tail water depth is needed to form a hydraulic jump? If a jump is formed, find its (a) type, (b) length, (c) head loss, (d) energy loss as a percentage of the initial energy, and (e) profile.

### Section-C

Note: Attempt any 2 questions from this section. (15×2=30)

- Q.3. (a) Draw neat sketches of various shapes of draft tubes. (5)

Q.4. (a)

A compound channel is symmetrical in cross section and has the following geometric properties. Main channel: Trapezoidal cross section, Bottom width =  $15.0 \text{ m}$ , Side slopes =  $1.5 \text{ H} : \text{V}$ , Bank full depth =  $3.0 \text{ m}$ , Manning's coefficient =  $0.03$ , Longitudinal slope =  $0.0009$  Flood plains: Width =  $75 \text{ m}$ , Side slope =  $1.5 \text{ H} : \text{V}$ , Manning's coefficient =  $0.05$ , Longitudinal slope =  $0.0009$ . Compute the uniform flow discharge for a flow with total depth of  $4.2 \text{ m}$  by using DCM with either (i) diagonal interface, or (ii) vertical interface procedures. (12)

- (b) A triangular channel with an apex angle of  $75^\circ$  carries a flow of  $1.2 \text{ m}^3/\text{s}$  at a depth of  $0.80 \text{ m}$ . If the bed slope is  $0.009$ , find the roughness coefficient of the channel. (03)

(4)

(5)

P.T.O.

- (i) Diameter of the impeller (outside diameter)
- (ii) Width of the impeller at outlet.

(09)

(6)