		www.	w.Firsti	Rankei	.com www.FirstRanker.c	om		
uptuonline.com	(Following Paper ID and Roll No. to be filled in your Answer Book) Paper ID :100503 Roll No. B.Tech. (SEM. V) THEORY EXAMINATION, 2015-16 ENVIRONMENTAL ENGINEERING-I				(i) What percentage of to losses in pipes?	total water de		
					(j) How much DO and water?	d BOD is de		
				ᆵ	Section-B			
				tuo	Attempt any five Parts:			
	: [Time:3 hours] [MaximumMan		uptuonline.com	uptuonline.com	Q.2 Explain various types of joints used			
	Section-A Q.1 Attempt all the parts. $(10\times2=20)$		ē.	<u>.</u>	system.			
			no:	no.	Q.3 Explain effects of air pollution in det			
aktuonline.com	(a) What are manholes?		X	0	Q.4 Differentiate between de supply pipes. A city has a	40		
		Which source or water contains maximum amount of turbidity?	N	<u>a</u>	water supply rate of 200 lpcd. Assum reaches the sewer, what will be the D'			
		Which type of pump is, commonly used hand pump? What is the function of scour valve?		aktuonline.com	9.5 Write a short note on various plumbin buildings and houses.			
	(d)			ne.	Q.6 The population of 5 dec	The population of 5 decades from 1		
		What is permissible limit of nitrates in drinking water?	aktuonline.com	com	given. Find out the population after of decades beyond the last known of			
		 Sewers are generally laid, starting from their point. 			arithmetic mean method. Year 1930 1940 1950			
	(g)	Pumps are connected to be in to double			Population 25,000 28,000	34,000 4		

COmaktuonline.com

uptuonline.com aktuonline.com

- (h) What are the causes of temporary hardness?
- emand contributes
- esired in drinking

- d in water supply
- ail.
- er pipes and water of 1,00,000 with a ning 75% of water WF in (m3/s)?
- ng fittings used in
- 1930 to 1970 are ne, two and three lecade by using

Year	1930	1940	1950	1960	1970	
Population	25,000	28,000	34,000	42,000	47,000	

NCE-503 aktuonline.com uptuonline.com

(2)

P.T.O aktuonline.com

the discharge and keep the head same.

aktuonline.com

Q.8 A combined sewer of circular section is to be designed for a city of population 1,00,000 and an area of 100 ha. The mean flow of the sewage from the city is 250 lpcd.

depth of 10 cm with Manings n=0.014.

upingtina erker.com

Figure isker's deanising velocity? What would be the www.FirstRanker.com

The critical rainfall intensity is 4 cm/hr. Take Manings coefficient as 0.012. Determine the gradient of the sewer from Manings equation to carry a peak flow with

design discharge of a 20 cm diameter sewer being laid at a slope of 0.004 and designed to carry discharge at a

a velocity of 1.2 m/s. Take k-0.48.

Q.9 What aer the types of sewerage system? Explain.

Section-C

Attempt any two parts:

 $(2 \times 15 = 30)$

Q.10 What is plume? Explain various plume behavior in detail with the help of neat sketches.

- Q.11 Discuss various population forecasting methods in detail.
- Q.12 Write short note on various methods used for analysis of complex pipe networks. Explain the Hardy Cross method in detail.

aptuonlin

www.FirstRanker.com

__×_

(3)

NCE-www.FirstRanker.com