

Printed Pages: 4

865/979

EEN-701/EEE-504

(Following Paper ID and Roll No. to be filled in your Answer Book)

Paper ID : 121703/121524

Roll No.

B.Tech.

(SEM. VII) THEORY EXAMINATION, 2015-16

ELECTRICAL INSTRUMENTATION & PROCESS  
CONTROL

[Time:3 hours]

Section-A

[Total Marks:100]

1. Attempt all parts. All parts carry equal marks. Write answer of each part in short. (10×2=20)
- (a) Differentiate between primary and secondary transducers with example.
  - (b) A thermistor has a characteristic temperature  $\beta$  of 3000 K. If its resistance is 100k  $\Omega$ , what will be its resistance at 600 K.
  - (c) Why platinum is preferred over gold to construct RTD?
  - (d) Define working principle of Hall Effect transducer.
  - (e) Discuss criterion for the selection of transmission channel in a telemetry system.

7200

(1)

P.T.O.

- (f) What is neutral zone in a ON/OFF controller.
- (g) What is the need of data transmission and telemetry.
- (h) Describe the working principle of LCD.
- (i) Discuss advantages of digital oscilloscope over analog oscilloscope.
- (j) What are the elements of process control.

**Section-B**

Attempt any five question from this section. (5×10=50)

- 2. What are different types of mechanical pressure sensing elements? Explain the measurement of pressure using capacitive transducer with the help of neat diagram.
- 3. What is strain gauge transducer? Give its applications.  
A strain gauge is bonded to a beam 0.1m long and has a cross sectional area 4cm<sup>2</sup>. Young's modulus for steel is 207 GN/m<sup>2</sup>. The strain gauge has an unstrained resistance of 240Ω and a gauge factor of 2.2. When a load is applied, the resistance of gauge changes by 0.013Ω. Calculate the changes in length of the steel beam and the amount of force applied to the beam.
- 4. Explain why it is essential to use radio frequency telemetry? Compare the salient features of PAM and PCM telemetry techniques.

7200

(2)

EEN-701/EEE-504

- 5. Describe the basic components of a magnetic tape recorder and explain direct recording technique of tape recording.
- 6. What is three term control action? What are the changes in the overall system dynamics when a derivative action is plugged in? What are the tunable parameters of a PID controller.

- 7. What is a proportional controller? Discuss its characteristics and advantages.

A proportional controller is used to control temperature within 50°C to 130°C. A set point is 73.5 °C. The set point is maintained with 50% as output of controller. Find the proportional offset which requires 55% of controller output when proportional gain is:(i)0.1(ii)10.0.

- 8. What are the advantages of Digital data acquisition system over Analog data acquisition system. Explain in brief the building blocks of Modern digital data acquisition system.

- 9. Write short notes on following:

- (i) Photoconductive Cell.
- (ii) Total Radiation Pyrometer.

7200

(3)

P.T.O.

**Section-C**

Attempt **any two** questions from this section. (15x2=30)

10. Explain the construction of resistance potentiometer used for the measurement of linear displacement. Derive the expression for output voltage.

A linear resistance potentiometer is 50mm long and is uniformly wound with a wire having a resistance of 10,000 ohms. Under normal conditions, the slider is at the centre of the potentiometer. Find the linear displacement when the resistance of the potentiometer as measured by a Wheatstone bridge for two cases is: (i) 3850 ohms (ii) 7560 ohms. Are the two displacements in the same direction?

11. Write short note on following:

- (i) DSO
- (ii) Smart sensors

12. (a) Describe the measurement of fluid velocity using ultrasonic flow meter. Derive the expression for velocity of fluid.
- (b) Explain different types of channels used for telemetry mentioning advantages and disadvantages of each.

—x—

7200

(4)

EEN-701/EEE-504