

Code: 9A01802

R09

B.Tech IV Year II Semester (R09) Regular & Supplementary Examinations April 2016

DESIGN & DRAWING OF IRRIGATION STRUCTURES

(Civil Engineering)

Time: 3 hours

Max. Marks: 70

Answer any ONE question
All questions carry equal marks

- 1 Design a cross drainage work to suit the following hydraulic particulars:

Canal:Discharge = $35 \text{ m}^3/\text{s}$

Bed width = 20.00 m

Bed level = +40.00

F.S.L = +42.00

Ultimate bed level = +39.75 (U.B.L)

Ultimate F.S.L = +42.50 (U.F.S.L)

Average velocity in the canal = $0.83 \text{ m}^3/\text{s}$

Left bank top width = 5.00 m

Right bank top width = 2.00 m

Canal side slopes both inside and outside are 2:1 in embankment with a minimum cover of 1 m over the hydraulic gradient. Top of canal bank = +43.50. Average ground level on flanks of drain = +38.00 and the bed level of the drain may also be taken as +38.00 at the point of crossing.

Drain:

Catchment area = 8 km^2 . The maximum computed discharge is worked out at $60 \text{ m}^3/\text{s}$ using a coefficient of $C = 15$ in Ryves formula. Maximum flood level of the drain at the site of crossing is +39.75. Average bed level of the drain at the site of crossing is +38.00. Hard soil suitable for the foundation is met +37.00. Also draw the plan, longitudinal and cross sections.

- 2 Design a sluice taking off from a tank irrigating 200 hectares at 1000 duty. The tank bund through which the sluice is taking off has a top width of 2 m with 2:1 side slopes. The top level of bank is +40.00 and the ground level at site is +34.50. Good hard soil for foundation is available at +33.50. The sill of the sluice at off-take is +34.00. The maximum water level in tank is 38.00. The full tank level is +37.00. Average low water level of the tank is +35.00. The details of the channel below the sluice are as under:

Bed level = +34.00

F.S.L = +34.50

Bed width = 1.25 m

Side slopes $1\frac{1}{2}$ to 1 with top of bank at +35.50

Draw the plan, longitudinal section and cross section.
