

Code: 9A03505

B.Tech III Year I Semester (R09) Supplementary Examinations June 2016

HEAT TRANSFER

(Mechanical Engineering)

Time: 3 hours

Max Marks: 70

Answer any FIVE questions

All questions carry equal marks

Use of heat transfer data book and steam tables is permitted in the examination hall

- 1 (a) Heat is generated within a sphere at $2.07 \times 10^8 \text{ W/m}^3$. The sphere is 8 cm in diameter. The surface temperature is 370 K. (i) Calculate the temperature at the center of the sphere. (ii) Calculate the temperature at a radial distance of 2 cm.
- (b) Define and distinguish between: (i) Steady state. (ii) Unsteady state. (iii) Transient state of heat transfer.
- 2 (a) The surface of steel plate measuring 0.9 m long \times 0.6 m wide \times 0.025 m thick is maintained at a uniform temperature of 300°C and the plate loses 250 W by radiation. If air is at 15°C temperature and $20 \text{ W/m}^2\text{K}$ convective heat transfer coefficient blows over the plate, calculate the temperature on inside surface of the plate. Take thermal conductivity of plate as 45 W/mK .
- (b) Derive expressions for temperature distribution during steady state heat conduction in a solid sphere.
- 3 (a) What is lumped mass model? Derive the equation for the temperature of a lumped body for the specified transient condition.
- (b) A thick bronze plate ($\alpha = 0.86 \times 10^{-5} \text{ m}^2/\text{s}$ and $K = 26 \text{ W/mK}$) is initially at a uniform temperature of 250°C . Suddenly the surface is exposed to a coolant at 25°C . Assuming $h = 150 \text{ W/m}^2\text{K}$, determine the temperature at 5 cm from the surface after 10 min of exposure.
- 4 (a) What is the significance of Grashof Number and Rayleigh Number?
- (b) Water is heated while flowing through 1.5 cm \times 3.5 cm rectangular cross section tube with a velocity of 1.2 m/s. The entering temperature of water is 40°C and the tube wall is maintained at 85°C . Determine length of the tube required to raise the temperature to 70°C .
- 5 (a) Why the mean temperature is to be considered instead of ambient temperature for internal flows? Explain
- (b) Air at 20°C is flowing along a heated flat plate at 150°C at a velocity of 3 m/sec. The plate is 2 m long and 1.5 m wide. Calculate the thickness of the hydrodynamic boundary layer and the skin friction coefficient at 30 cm from the leading edge of the plate. Kinematic viscosity of air at 20°C is $15.06 \times 10^{-6} \text{ m}^2/\text{s}$.
- 6 (a) Discuss the different types of processes for condensation of vapours on solid surfaces with suitable diagrams.
- (b) Water is boiled at the rate of 25 kg/h in a polished copper pan, 280 mm in diameter, at atmospheric pressure. Assuming nucleate boiling conditions, calculate the temperature of the bottom surface of the pan.
- 7 (a) Define heat exchanger effectiveness and explain its significance.
- (b) In a counter flow double pipe heat exchanger water is heated from 40°C to 80°C with an oil entering at 105°C and leaving at 70°C . Taking the overall heat transfer coefficient as $300 \text{ W/m}^2\text{K}$ and the water flow rate as 0.1 kg/s. Calculate the heat exchanger area.
- 8 (a) State Kirchhoff's and Wien's laws of thermal radiation. Derive the Wien's law from basic Planck's distribution law.
- (b) A gray surface is maintained at a temperature of 860°C . If the maximum spectral emissive power at that temperature is $1.5 \times 10^{10} \text{ W/m}^2$, determine the emissivity of the body and the wavelength corresponding to maximum spectral intensity of radiation.