

## Code: 13A01303

B.Tech II Year I Semester (R13) Regular & Supplementary Examinations December 2015

# FLUID MECHANICS

(Civil Engineering)

Time: 3 hours

Max. Marks: 70

www.FirstRanker.com

#### PART – A

(Compulsory Question)

\*\*\*\*\*

- 1 Answer the following: (10 X 02 = 20 Marks)
  - (a) Define viscosity and state the reason for variation in behavior of viscosity of gases and liquids w.r.t temperature.
  - (b) Distinguish between static pressure and total pressure.
  - (c) State the stability criteria for a submerged body in unstable and neutral equilibrium positions.
  - (d) Distinguish between uniform and non-uniform flow.
  - (e) What does Hydraulic gradient line represent?
  - (f) What is a mouth piece?
  - (g) Name the forces considered in deriving the momentum equation.
  - (h) Why the triangular weir is more suitable than a rectangular weir for discharge measurement?
  - (i) Distinguish between minor and major losses in pipe flow.
  - (j) What do you understand by the term "Mixing length"?

#### PART – B

(Answer all five units, 5 X 10 = 50 Marks)

# UNIT - I

- 2 (a) Derive the formula for capillary rise of a fluid in the annulus of two concentric glass tubes of radii R<sub>0</sub> and R<sub>i</sub> respectively.
  - (b) A flat plate of area  $0.5 \text{ m}^2$  moves through oil between two large fixed parallel planes 8 cm apart. If the velocity of the plate is 0.5 m/sec and the oil has specific gravity 0.8 and kinematic viscosity of 0.45 x  $10^{-4} \text{ m}^2$ /sec, calculate the drag force acting on the fluid. Assume the plate is parallel and is equidistant from both the planes.

#### OR

- 3 (a) State the hydrostatic law for an incompressible fluid.
  - (b) Determine the magnitude and direction of the resultant force acting on a cylindrical roller gate of 2.5 m diameter and length 5 m due to the water when the gate is placed on the dam such that water is just going to spill over it.

# UNIT – II

- 4 (a) Explain the terms: (i) Center of buoyancy. (ii) Meta-center. (iii) Center of gravity.
  - (b) A rectangular box of 24 m<sup>2</sup> cross sectional area and 2 m height having a weight of 400 kN is immersed in freshwater of density 1000 kg/m<sup>3</sup>, calculate the depth of immersion of box.

#### OR

- 5 (a) Define stream function and velocity potential and express the condition for irrotational flow in terms of stream function and velocity potential.
  - (b) In a steady two dimensional incompressible flow, the velocity component in the X direction is  $u = 4x^2 + y^2$ . Find the velocity component 'v 'in Y direction. Assume at Y = 0, v = 0. Also find the direction of the stream line with respect to X axis at a point (2, 2).

Contd. in page 2

ww.FirstRanker.com

#### Code: 13A01303

www.FirstRanker.com



### UNIT – III

- 6 (a) What is free vertex flow? Give some practical examples of its occurrence.
  - (b) A 20 cm diameter pipe carries water under a head of 20 m with a velocity of 3.5 m/sec. If the axis of the pipe turns through 30°, determine the magnitude and direction of the resultant force on the bend.

#### OR

- 7 (a) With a neat sketch, explain the venturimeter principle and derive an expression for discharge through it.
  - (b) A venturimeter of 0.6 contraction ratio is fitted to a 100 mm diameter horizontal pipe. The head of water on the meter under no flow condition is 3 m gauge. Find the rate of flow when the throat pressure is 2 m of water absolute. Assume coefficient of discharge for venturimeter as 0.98.

#### UNIT – IV

- Distinguish between free and submerged orifice. 8 (a)
  - (b) An orifice of 10 cm diameter under a head of 3 m discharges 35 liters per second of water. The jet from the orifice exerts a force of 300 N on a flat plate placed normal to it. Determine the theoretical discharge, coefficient of velocity and coefficient of contraction.

#### OR

- 9 (a) What do you understand by Aeration of Nappe and why is it required?
  - (b) Water flows through a rectangular channel 1 m wide and 0.5 m deep and then over a Cipolletti weir of crest length 60 cm. If the water level in the channel is 22.5 cm above the weir crest, calculate the discharge over the weir: (i) Neglecting the velocity of approach. (ii) Considering the velocity of the approach. Take  $C_d = 0.6$  and assume angle of inclination for Cipolletti weir as  $\tan^{-1}(\frac{1}{d})$ .

# UNIT – V

- (a) Show that in a laminar flow through pipe the average velocity occurs at 0.707R from the center of the 10 pipe of radius R if velocity distribution across the pipe is given by  $U = \frac{1}{4\mu} \left(\frac{-dp}{dx}\right) (R^2 - r^2)$ 
  - Water is flowing through a 25 cm diameter pipe with friction factor f = 0.04. A shear stress at a point (b) 5 cm from the pipe axis is 125Pa. calculate the shear stress at the pipe wall assuming the variation of  $U = \frac{1}{4\mu} \left( \frac{dp}{dx} \right) \left( R^2 - r^2 \right)$ velocity across the pipe follows

- Derive an expression for head loss due to sudden enlargement in a pipe flow. 11 (a)
  - At sudden enlargement of water line from 25 cm to 50 cm diameter pipe, the hydraulic gradient raises (b) by 1 cm, calculate the rate of flow.

\*\*\*\*\*