Set No. 2

I B.Tech Examinations, December 2010 PROCESS ENGINEERING PRINCIPLES Bio-Technology

Time: 3 hours Max Marks: 80

Answer any FIVE Questions All Questions carry equal marks

- 1. (a) Explain the following terms as they are applied to a centrifugal pump
 - i. static suction lift

Code No: R07A12301

- ii. static suction head
- iii. static discharge head
- iv. total static head.
- (b) Describe the working principle of any one type of rotary pump with a neat sketch. [8+8]
- 2. (a) Explain the purpose of using a non return valve in the suction pipe of a centrifugal pump.
 - (b) Discuss about the important flow meters used in industry. What are the advantages and disadvantages over each other?
 - (c) What is the use of foot valve and strainer in centrifugal pump? [6+8+2]
- 3. (a) Explain the development of boundary layer in a flat plate.
 - (b) Distinguish between laminar and turbulent flow.

[10+6]

- 4. (a) If the velocity distribution of a fluid over a plate is given by $u=(3/4)y-y^2$ where u is the velocity in metre per sec at a distance of y meters above the plate, determine the shears stress at y=0.15 meters.
 - Take the dynamic viscosity of the fluid as 8.5×10^{-5} kg-sec/m.
 - (b) Classify the types of fluid.

[8+8]

- 5. Write short notes on:
 - (a) Specific cake resistance
 - (b) Equivalent cake thickness
 - (c) Filter aid
 - (d) Factors that effect the filtration rate.

[4+4+4+4]

6. (a) Acetylene gas is formed according to the equation:

$$CaC_2 + 2H_2O - - - - > C_2H_2 + Ca(OH)_2$$

Calculate the number of hours of service that can be derived from 1.0 kg of carbide in an acetylene lamp burning 60 liter of gas per hour at 30°C and a pressure of 725 mm Hg. Assume ideal gas law.

Set No. 2

(b) A solution of NaCl in water contains 300 gm of NaCl per liter at 30° C. The density of solution at 30° C is 1.152 gms/cm³, calculate the following:

- i. Volumetric percent of water.
- ii. Composition in mole percent.

[8+8]

- 7. (a) Define Fanning friction factor and Darcy's friction factor
 - (b) Define equivalent diameter

Code No: R07A12301

- (c) Blassius law for friction factor
- (d) Write short notes on friction factor charts.

[4+4+4+4]

- 8. (a) Water at 60°C is pumped from a reservoir to the top of a mountain through a 15 cm pipe at a velocity of 3.5 m/s. The pipe discharges into the atmosphere at a level of 1000 m above the level in the reservoir. The pipe itself is 1500 m long. If the overall efficiency of the pipe is 65 %. Calculate the power requirement?
 - (b) Explain the concept of hydrostatic pressure.

[12+4]

Code No: R07A12301

R07

Set No. 4

I B.Tech Examinations, December 2010 PROCESS ENGINEERING PRINCIPLES Bio-Technology

Time: 3 hours Max Marks: 80

Answer any FIVE Questions All Questions carry equal marks

- 1. (a) Explain the purpose of using a non return valve in the suction pipe of a centrifugal pump.
 - (b) Discuss about the important flow meters used in industry. What are the advantages and disadvantages over each other?
 - (c) What is the use of foot valve and strainer in centrifugal pump? [6+8+2]
- 2. (a) Explain the following terms as they are applied to a centrifugal pump
 - i. static suction lift
 - ii. static suction head
 - iii. static discharge head
 - iv. total static head.
 - (b) Describe the working principle of any one type of rotary pump with a neat sketch. [8+8]
- 3. (a) Explain the development of boundary layer in a flat plate.
 - (b) Distinguish between laminar and turbulent flow.

[10+6]

- 4. (a) If the velocity distribution of a fluid over a plate is given by $u=(3/4)y-y^2$ where u is the velocity in metre per sec at a distance of y meters above the plate, determine the shears stress at y=0.15 meters.
 - Take the dynamic viscosity of the fluid as 8.5×10^{-5} kg-sec/m.
 - (b) Classify the types of fluid.

[8+8]

- 5. Write short notes on:
 - (a) Specific cake resistance
 - (b) Equivalent cake thickness
 - (c) Filter aid
 - (d) Factors that effect the filtration rate.

[4+4+4+4]

6. (a) Acetylene gas is formed according to the equation:

$$CaC_2 + 2H_2O - - - - > C_2H_2 + Ca(OH)_2$$

Calculate the number of hours of service that can be derived from 1.0 kg of carbide in an acetylene lamp burning 60 liter of gas per hour at 30^oC and a pressure of 725 mm Hg. Assume ideal gas law.

Set No. 4

(b) A solution of NaCl in water contains 300 gm of NaCl per liter at 30° C. The density of solution at 30° C is 1.152 gms/cm³, calculate the following:

i. Volumetric percent of water.

Code No: R07A12301

ii. Composition in mole percent.

[8+8]

- 7. (a) Water at 60°C is pumped from a reservoir to the top of a mountain through a 15 cm pipe at a velocity of 3.5 m/s. The pipe discharges into the atmosphere at a level of 1000 m above the level in the reservoir. The pipe itself is 1500 m long. If the overall efficiency of the pipe is 65 %. Calculate the power requirement?
 - (b) Explain the concept of hydrostatic pressure.

[12+4]

- 8. (a) Define Fanning friction factor and Darcy's friction factor
 - (b) Define equivalent diameter
 - (c) Blassius law for friction factor
 - (d) Write short notes on friction factor charts.

[4+4+4+4]

Set No. 1

I B.Tech Examinations, December 2010 PROCESS ENGINEERING PRINCIPLES Bio-Technology

Time: 3 hours Max Marks: 80

Answer any FIVE Questions All Questions carry equal marks

- 1. (a) Explain the development of boundary layer in a flat plate.
 - (b) Distinguish between laminar and turbulent flow.

[10+6]

- 2. (a) Explain the purpose of using a non return valve in the suction pipe of a centrifugal pump.
 - (b) Discuss about the important flow meters used in industry. What are the advantages and disadvantages over each other?
 - (c) What is the use of foot valve and strainer in centrifugal pump? [6+8+2]
- 3. Write short notes on:

Code No: R07A12301

- (a) Specific cake resistance
- (b) Equivalent cake thickness
- (c) Filter aid
- (d) Factors that effect the filtration rate.

[4+4+4+4]

- 4. (a) Define Fanning friction factor and Darcy's friction factor
 - (b) Define equivalent diameter
 - (c) Blassius law for friction factor
 - (d) Write short notes on friction factor charts.

[4+4+4+4]

- 5. (a) If the velocity distribution of a fluid over a plate is given by $u=(3/4)y-y^2$ where u is the velocity in metre per sec at a distance of y meters above the plate, determine the shears stress at y=0.15 meters.

 Take the dynamic viscosity of the fluid as 8.5×10^{-5} kg-sec/m.
 - (b) Classify the types of fluid.

[8+8]

- 6. (a) Water at 60°C is pumped from a reservoir to the top of a mountain through a 15 cm pipe at a velocity of 3.5 m/s. The pipe discharges into the atmosphere at a level of 1000 m above the level in the reservoir. The pipe itself is 1500 m long. If the overall efficiency of the pipe is 65 %. Calculate the power requirement?
 - (b) Explain the concept of hydrostatic pressure.

[12+4]

7. (a) Explain the following terms as they are applied to a centrifugal pump

Set No. 1

i. static suction lift

Code No: R07A12301

- ii. static suction head
- iii. static discharge head
- iv. total static head.
- (b) Describe the working principle of any one type of rotary pump with a neat sketch. [8+8]
- 8. (a) Acetylene gas is formed according to the equation:

 $CaC_2 + 2H_2O - - - - > C_2H_2 + Ca(OH)_2$

Calculate the number of hours of service that can be derived from 1.0 kg of carbide in an acetylene lamp burning 60 liter of gas per hour at 30°C and a pressure of 725 mm Hg. Assume ideal gas law.

- (b) A solution of NaCl in water contains 300 gm of NaCl per liter at 30°C. The density of solution at 30°C is 1.152 gms/cm³, calculate the following:
 - i. Volumetric percent of water.
 - ii. Composition in mole percent.

[8+8]

Set No. 3

I B.Tech Examinations, December 2010 PROCESS ENGINEERING PRINCIPLES Bio-Technology

Time: 3 hours Max Marks: 80

Answer any FIVE Questions All Questions carry equal marks

- 1. (a) Water at 60°C is pumped from a reservoir to the top of a mountain through a 15 cm pipe at a velocity of 3.5 m/s. The pipe discharges into the atmosphere at a level of 1000 m above the level in the reservoir. The pipe itself is 1500 m long. If the overall efficiency of the pipe is 65 %. Calculate the power requirement?
 - (b) Explain the concept of hydrostatic pressure.

[12+4]

- 2. (a) Define Fanning friction factor and Darcy's friction factor
 - (b) Define equivalent diameter
 - (c) Blassius law for friction factor
 - (d) Write short notes on friction factor charts.

[4+4+4+4]

3. Write short notes on:

Code No: R07A12301

- (a) Specific cake resistance
- (b) Equivalent cake thickness
- (c) Filter aid
- (d) Factors that effect the filtration rate.

[4+4+4+4]

- 4. (a) Explain the following terms as they are applied to a centrifugal pump
 - i. static suction lift
 - ii. static suction head
 - iii. static discharge head
 - iv. total static head.
 - (b) Describe the working principle of any one type of rotary pump with a neat sketch. [8+8]
- 5. (a) Acetylene gas is formed according to the equation:

 $CaC_2 + 2H_2O - - - - > C_2H_2 + Ca(OH)_2$

Calculate the number of hours of service that can be derived from $1.0~\rm kg$ of carbide in an acetylene lamp burning 60 liter of gas per hour at $30^{\rm o}{\rm C}$ and a pressure of 725 mm Hg. Assume ideal gas law.

- (b) A solution of NaCl in water contains 300 gm of NaCl per liter at 30°C. The density of solution at 30°C is 1.152 gms/cm³, calculate the following:
 - i. Volumetric percent of water.

Set No. 3

ii. Composition in mole percent.

[8+8]

- 6. (a) If the velocity distribution of a fluid over a plate is given by $u=(3/4)y-y^2$ where u is the velocity in metre per sec at a distance of y meters above the plate, determine the shears stress at y=0.15 meters.

 Take the dynamic viscosity of the fluid as 8.5×10^{-5} kg-sec/m.
 - (b) Classify the types of fluid.

Code No: R07A12301

[8+8]

- 7. (a) Explain the development of boundary layer in a flat plate.
 - (b) Distinguish between laminar and turbulent flow.

[10+6]

- 8. (a) Explain the purpose of using a non return valve in the suction pipe of a centrifugal pump.
 - (b) Discuss about the important flow meters used in industry. What are the advantages and disadvantages over each other?
 - (c) What is the use of foot valve and strainer in centrifugal pump? [6+8+2]

