

Code No: R1621016

R16**SET - 1****II B. Tech I Semester Supplementary Examinations, May - 2018****FLUID MECHANICS**

(Civil Engineering)

Time: 3 hours

Max. Marks: 70

Note: 1. Question Paper consists of two parts (**Part-A** and **Part-B**)2. Answer **ALL** the question in **Part-A**3. Answer any **FOUR** Questions from **Part-B****PART -A**

1.
 - a) Define specific volume and specific gravity of a fluid.
 - b) What is center of pressure?
 - c) What are the applications of momentum equation?
 - d) Differentiate smooth and rough flows.
 - e) Define Vena-contracta
 - f) Define drag and lift force of an object immersed in a liquid.

PART -B

2.
 - a) Calculate specific weight, density and specific gravity of two liters of a liquid which weigh 15 N.
 - b) Define pressure. Obtain an expression for the pressure intensity at a point in a fluid.
3.
 - a) Differentiate between:
 - (i) Steady and Unsteady flow
 - (ii) Uniform and non uniform flow
 - (iii) Laminar and turbulent flow
 - (iv) Rotational and irrotational flow
 - b) Derive the equation of continuity for one dimensional flow of an incompressible fluid.
4.
 - a) Write Euler's equation of motion along a streamline and integrate it to obtain Bernoulli's equation. State all assumptions made.
 - b) What are the surface and body forces associated with fluid flow? How are they incorporated in Euler's equation?
5.
 - a) What are hydraulic grade line and total energy line? How do you draw the same?
 - b) What do you mean by pipe in series and pipes in parallel?
6.
 - a) Define velocity of approach. How can you account for it while computing the discharge over weirs?
 - b) A pitot-tube is inserted in a pipe of 300mm diameter. The static pressure in pipe is 100mm of mercury (vacuum). The stagnation pressure at the center of the pipe, recorded by the pitot tube is 0.981 N/cm^2 . Calculate the rate of flow of water through pipe, if the mean velocity of flow is 0.85 times the central velocity. Take $C_v = 0.98$.

Code No: R1621016

R16**SET - 1**

7. a) Define boundary layer and explain the fundamental causes of its existence. Also discuss the various methods of controlling the boundary layer.
- b) It is required to determine the frictional drag of a submarine. The length of the hull is 75m and its surface area is 3000m^2 . The submarine is travelling at a constant speed of 5m/s. critical Reynolds number at which the flow in the boundary layer changes from laminar to turbulent is 5×10^5 . Assuming that the boundary layer at the leading edge is laminar, obtain the frictional drag and the power required to propel the submarine at 5m/s. take $\nu = 1 \times 10^{-6}\text{m}^2/\text{s}$ and $\rho = 1000\text{kg}/\text{m}^3$.