

www.FirstRanker.com

## Code No: R32042



Set No: 1

Max Marks: 75

III B.Tech. II Semester Supplementary Examinations, January -2014 MICROWAVE ENGINEERING

(Electronics and Communication Engineering)

Time: 3 Hours

## Answer any FIVE Questions All Questions carry equal marks \*\*\*\*\*

1. (a) What are the various applications of Microwaves? [5+5+5]

( b ) Sketch the Field lines of Rectangular waveguide for  $TE_{10}$  and  $TM_{20}$  modes.

(c) Derive the equation for impedance of a Rectangular waveguide in TE mode.

- 2. (a) Derive the expressions for the field components Ey, Hx and Hy of rectangular cavity. [8+7]
   (b) Draw the structure of Microstrip line and find its characteristic impedance?
- 3. Explain the following microwave components: [5+5+5]
  (a) Coupling mechanisms (b) waveguide attenuators (c) waveguide Phase shifters
- 4. (a) How the Ferrites are used in Isolators? Explain any one of such an Isolator with neat sketches. [8+7]
  (b) Derive the S-matrix of Magic Tee and write its applications.
- 5. ( a ) What are the advantages of Reentrant Cavities? How these are used in Two Cavity Klystrons?

( b ) Draw the output power characteristics of Reflex Klystron and explain how oscillating modes are formed.

( c ) Explain the Electronic tuning in Reflex Klystron and compare it with Mechanical tuning. [5+5+5]

6. (a) What are the different types of slow wave structures? What are the different characteristics of them.

(b) Explain how the Cross-field is used to obtain oscillations in Magnetrons? [7+8]

7. ( a ) How Gunn diode is used as a oscillator? Explain its working with suitable diagram.

(b) Draw the characteristics of TRAPATT Diode and explain it. [8+7]

8. (a) What type of precautions has to be considered while measuring parameters at Microwave frequencies?

(b) Explain the method of measurement of High and Low VSWR at Microwave frequencies. [5+10]



www.FirstRanker.com

Code No: R32042



Set No: 2

Max Marks: 75

[5+5+5]

III B.Tech. II Semester Supplementary Examinations, January -2014 MICROWAVE ENGINEERING

(Electronics and Communication Engineering)

**Time: 3 Hours** 

Answer any FIVE Questions All Questions carry equal marks \*\*\*\*\*

- - (b) Explain how the Magic Tee used as a Duplexer? [8+7]
- 4. (a) Derive the S-matrix of H-plane Tee.
  - (b) How a circulator can be used as an Isolator?
  - (c) What is Gyrator? How it works?
- 5. (a) Explain how velocity modulation converts into current modulation in Two Cavity Klystron amplifier? [8+7]
   (b) Derive the expression for Electronic Admittance of Reflex Klystron Oscillator?
- 6. (a) Explain the amplification process in TWT with suitable structural diagram.
  - (b) How to separate a  $\pi$  mode in Magnetrons?
  - (c) How to suppress an oscillations in TWT? [7+4+4]
- 7. (a) What are the different modes of operation for a Gunn diode? Explain them(b) Draw the characteristics of IMPATT diode and explain them. [8+7]
- 8. ( a ) Draw the basic Bench Setup for Microwave measurements and explain the significance of each component. [8+7]

(b) How the Microwave Power can be measured? Explain any one of such method.

\*\*\*\*



www.FirstRanker.com

Code No: R32042



Set No: 3

III B.Tech. II Semester Supplementary Examinations, January -2014 **MICROWAVE ENGINEERING** 

(Electronics and Communication Engineering)

**Time: 3 Hours** 

## Answer any FIVE Questions

Max Marks: 75

All Questions carry equal marks \*\*\*\*\*

1. (a) Why TEM mode cannot exist in a Rectangular Waveguide? (b) Calculate the attenuation constant at 6 GHz for an air-filled, 2 X 4 cm rectangular guide.

(c) Derive the equation for characteristic impedance of rectangular waveguide in TM mode. [5+5+5]

- 2. (a) Draw the attenuation characteristics of air-filled circular wave guide in  $TE_{01}$  mode compare the operation of it with other modes.
  - (b) Define the unloaded Q of the rectangular cavity and derive its expression. [7+8]
- 3. (a) Explain the working of Rotary Vane type Phase shifter with neat sketch. (b) A matched generator ( $Z_G=Z_O$ ) with an available power of one watt is connected to the H arm of a magic tee. The E arm is match terminated and the length of the coplanar arms are the same. Calculate the power delivered to the terminations at ports 1,2 and 3 and the power reflected at port 4 when ports 1 and 2 are terminated in the following manner : 2

$$Z_{L1} = 2.4 Z_0$$
 and  $Z_{L2} = 0.6 Z_0$ . [8+7]

- 4. (a) Explain the working of circulator based on the principle of Faraday rotation. (b) Prove that  $|S_{13}| = |S_{24}|$  and  $|S_{14}| = |S_{23}|$  in an ideal Directional Coupler. [8+7]
- 5. (a) How Microwave tubes are classified? Give them with examples. [4+4+7](b) How the frequency of oscillations is changed in Reflex klystron Oscillator?
  - (c) Explain the process of Bunching in Reflex Klystron with applegate diagram.
- 6. (a) Derive the expression for Gain of TWT. [7+8] (b) Explain the principle of working of 8-Cavity Cylindrical Travelling wave Magnetron.
- 7. (a) What are the Transferred Electron Devices? Write applications of them. [7+8] (b) Explain the principle of working of IMPATT diode with suitable band structure.
- 8. (a) How the Q of the Cavity can be measured at Microwave frequencies?
  - (b) Explain the Bolometer method of power measurement. [8+7] \*\*\*\*\*



www.FirstRanker.com

Code No: R32042



Set No: 4

Max Marks: 75

III B.Tech. II Semester Supplementary Examinations, January -2014 MICROWAVE ENGINEERING

(Electronics and Communication Engineering)

Time: 3 Hours

Answer any FIVE Questions All Questions carry equal marks \*\*\*\*\*

- 1. (a) Derive the equations for Electric Fields of Rectangular Waveguide in TM mode. (b) Calculate the cutoff frequencies for  $TE_{11}$ ,  $TE_{20}$  and  $TM_{20}$  modes for a 1X4 cm rectangular guide is loaded with a 0.2cm wide dielectric having  $\epsilon_R=9$ . [9+6]
- 2. ( a ) Sketch the E & H field lines of circular waveguide in  $TE_{11},\,TE_{21}$  and  $TM_{01}$  modes.

(b) A rectangular cavity resonates in the  $TM_{111}$  mode at 5 GHz. Given a=8cm and b=6 cm, Calculate the resonant frequencies for the  $TE_{101}$ ,  $TE_{102}$  and  $TE_{111}$  mode. Assume an air-filled cavity. [7+8]

- 3. (a) What are the different types of Attenuators? Explain their operation with suitable diagrams.
  (b) A 25W signal is incident on port 2 of a directional coupler. Calculate the power out of ports 1 and 4 if the coupling is 33dB and the directivity is 24dB.
  (c) Draw the structure of E-Plane Tee and write its properties. [7+4+4]
- 4. (a) What is Faraday Rotation? How it is used for Isolation?
  (b) Derive the S-matrix for Directional Coupler. Write the applications of Directional coupler. [8+7]
- 5. (a) What are the limitations of conventional tubes at microwave frequencies? How to overcome them?
  (b) Determine the expression for output power and efficiency of Two cavity klystron amplifier. [7+8]
- 6. (a) What are the Four Propagation Constants? Discuss the nature of them.
  (b) Derive the expression for Hull Cut-off condition in 8 cavity Cylindrical Magnetron. [7+8]
- 7. (a) Draw the V-I characteristics of Gunn Diode and explain how negative resistance region is obtained?
  (b) Explain the working of TRAPATT diode with suitable band structure. [8+7]
- 8. (a) What is Slotted Section? How it is used in Microwave Measurements?
  (b) How the attenuation of any Microwave component is measured? [7+8]