

Code No: RT22013

R13**SET - 1**

II B. Tech II Semester Supplementary Examinations, April-2018
STRENGTH OF MATERIALS - II
(Civil Engineering)

Time: 3 hours

Max. Marks: 70

- Note: 1. Question Paper consists of two parts (**Part-A** and **Part-B**)
2. Answer **ALL** the question in **Part-A**
3. Answer any **THREE** Questions from **Part-B**
- ~~~~~

PART -A

1. a) What is Mohr's circle of stresses? (4M)
- b) Draw springs in series and springs in parallel (4M)
- c) What are the different types of columns? (3M)
- d) Define bending stress & Direct stress (4M)
- e) What are the stresses in beam subjects to unsymmetrical bending? (4M)
- f) Define degree of freedom (3M)

PART -B

2. Derive expressions for principal stresses, principal planes and max shear stress if there are like direct stresses accompanied by a state of simple shear (16M)
3. A shaft transmits 300kW power at 120rpm. Determine the necessary diameter of solid circular shaft and the necessary diameter of hollow circular section, the inside diameter being 2/3 of the external diameter. The allowable shear stress is 70N/mm^2 . Taking the density at material as 77N/m^3 , calculate the %saving in the shaft if hollow shaft is used. (16M)
4. A column having a T section with a flange 120 mm x 16 mm and web 150 mm x 16mm is 3m long. Assuming the column to be hinged at both ends, find the crippling load by using Euler's formula. $E = 2 \times 10^6 \text{ Kg/cm}^2$ (16M)
5. A beam of rectangular cross section is subjected to pure bending with a moment of 20kNm. The trace of the plane of loading is inclined at 45° to the YY axis of the section. Identify the N.A of the section and calculate the bending stress induced at each corner of the beam section (16M)

Code No: RT22013

R13**SET - 1**

6. a) Explain in brief how stresses in beams due to unsymmetric bending is considered. (8+8M)
b) Explain in brief the method of locating shear centre
7. Determine the forces in all the members of the frame by method of joints. (16M)

