

Code No: RT32035

**R13****SET - 1****III B. Tech II Semester Supplementary Examinations, November -2018****HEAT TRANSFER**

(Mechanical Engineering)

Time: 3 hours

Max. Marks: 70

Note: 1. Question Paper consists of two parts (**Part-A** and **Part-B**)2. Answering the question in **Part-A** is compulsory3. Answer any **THREE** Questions from **Part-B**

\*\*\*\*\*

**PART -A**

- 1 a) State the Newton's law of cooling. [3M]
- b) Under what conditions can a plane wall be treated as a semi-infinite medium? [4M]
- c) How is Reynolds analogy expressed? What is the value of it? What are its limitations? [3M]
- d) What is forced convection? How does it differ from natural convection? Is convection caused by winds forced or natural convection? [4M]
- e) Can the logarithmic mean temperature difference of a heat exchanger be a negative quantity? Explain [4M]
- f) State and explain Planck, Wien, Kirchoff laws. [4M]

**PART -B**

- 2 a) Distinguish between the basic laws of heat transfer with examples? [4M]
- b) An insulated pipe of 50 mm outside diameter ( $\epsilon=0.8$ ) is laid in a room at  $30^{\circ}\text{C}$ . If the surface temperature is  $250^{\circ}\text{C}$  and the convective heat transfer coefficient is  $10 \text{ W/m}^2\text{K}$ . Calculate the heat loss per unit length of pipe. [8M]
- c) Consider an alloy of two metals whose thermal conductivities are  $k_1$  and  $k_2$ . will the thermal conductivity of the alloy be less than  $k_1$ , greater than  $k_2$ , or between  $k_1$  and  $k_2$ . Explain. [4M]
- 3 a) Explain how biot number help in transient conduction problem. [3M]
- b) Derive expression for critical thickness of insulation for a cylinder. [8M]
- c) What are heisleir charts? Under what conditions heislier charts are used in heat transfer problems. [5M]
- 4 a) Discuss the formation of velocity boundary layer for flow of fluid through a circular cross section pipe. [8M]
- b) Air at 1atm and  $30^{\circ}\text{C}$  is forced through a horizontal 30mm diameter 0.5m Long at an average velocity of 0.25m/s. The tube wall is maintained at  $137^{\circ}\text{C}$ . Calculate i) the heat transfer coefficient and ii) percentage error if the calculation is made strictly on the basis of laminar forced convection. [8M]
- 5 a) Derive NTU of parallel flow and counter flow heat exchangers. [8M]
- b) A flow of 0.1kg/s of exhaust gases at  $70^{\circ}\text{K}$  from a gas turbine is used to preheat the incoming air, which is at the ambient temperature of  $30^{\circ}\text{K}$ . It is desired to cool the exhaust to  $40^{\circ}\text{K}$  and it is estimated that an overall heat coefficient of  $30 \text{ W/m}^2\text{K}$  can be achieved in an appropriate exchanger. Determine the area required for a counter flow heat exchanger. Take the specific heat of exhaust gasses the same as for air, Which is  $1000 \text{ J/kg.K}$ . [8M]

1 of 2



Code No: RT32035

**R13****SET - 1**

- 6 a) Distinguish between filmwise and dropwise condensation. Which of the two gives a higher heat transfer coefficient? Why? [8M]
- b) Determine the stable film boiling heat transfer coefficient for the film boiling of saturated water at atmospheric pressure on an electrically heated 1.6 mm diameter horizontal platinum wire with a temperature difference  $T_s - T_{sat} = 225^\circ\text{C}$ . What would be power dissipation per unit length of the heater? [8M]
- 7 a) Distinguish between [8M]
- i) A black body Vs gray body
  - ii) Specular Vs diffuse surfaces
  - iii) Absorptivity Vs emissivity of a surface
  - iv) Total emissivity Vs equilibrium emissivity
- b) A pipe carrying steam having an outside diameter 20cm runs in a large room, and is exposed to air at a temperature of  $30^\circ\text{C}$ . The pipe surface temperature is  $200^\circ\text{C}$ . Find the heat loss per meter length of the pipe by convection and radiation taking the emissivity of the pipe surface as 0.8. [8M]

\*\*\*\*\*