

Code No: **RT41025**

R13

Set No. 1

IV B.Tech I Semester Supplementary Examinations, February - 2019 INSTRUMENTATION

(Common to Electrical and Electronics Engineering and Mechanical Engineering)
Time: 3 hours

Max. Marks: 70

Question paper consists of Part-A and Part-B Answer ALL sub questions from Part-A Answer any THREE questions from Part-B *****

PART-A (22 Marks)

1.	a)	List out the dynamic characteristics of an instrument.	[3]
	b)	What are the properties of a passive transducer?	[4]
	c)	How strain can be measured?	[3]
	d)	What are the performance characteristics of digital voltmeters?	[4]
	e)	What is the function of vertical deflection plate in CRO?	[4]
	f)	Discuss the applications of Wave analyzers.	[4]
		$\underline{\mathbf{PART-B}} \ (3x16 = 48 \ Marks)$	
2.	a)	Classify the different types of signals and explain them with an example of each.	[8]
	b)	The value of a resistance is 5 k Ω , while measurements yield a value of 4.91 k Ω	
		calculate (i) relative accuracy of measurement (ii) percentage accuracy.	[8]
3.	a)	Explain in detail about the factors to be considered while selecting a transducer.	[8]
	b)	Discuss in detail about the advantages and limitations of Thermistor.	[8]
	,		507
4.	a)	Explain in detail about the advantages and disadvantages of magnetic flow meter.	[8]
	b)	Explain in detail about the principles used in torque measuring transducers.	[8]
_	۵)	With the help of a black discussion and a microscope	
5.	a)	With the help of a block diagram, explain the operation of a microprocessor	F01
	b)	based ramp type digital voltmeter.	[8]
	b)	A 3 ½ digital voltmeter has an accuracy of ± 0.5 % of reading ± 1 digit. What is	
		the possible error in volts when the instrument is reading 4 V on the 10 V range? What is the possible error in volts while reading 0.12 V on the 10 V range?	Γ Q 1
		what is the possible error in voits with a reading 0.12 v on the 10 v range?	[8]
6.	a)	Draw the block diagram of sampling oscilloscope and explain the working.	[8]
0.	b)	The Lissajous pattern on a CRO is stationary and has five horizontal and two	[O]
	0)	vertical tangencies. The frequency of horizontal input is 600 Hz. Determine the	
		frequency of vertical input and draw the pattern.	[8]
		The state of the s	L-J
7.	a)	Explain the operation of Heterodyne Wave analyzer with the help of its block	[8]
	•	diagram.	_
	b)	Discuss in detail about Peak reading voltmeters along with its significance.	[8]
		1 of 1	
		- 	