

Roll No.

Total No. of Pages : 02

Total No. of Questions : 09

B.Tech.(ANE) (Sem.-7,8)
AEROELASTICITY
Subject Code : ANE-412
M.Code : 70494

Time : 3 Hrs.

Max. Marks : 60

INSTRUCTION TO CANDIDATES :

1. SECTION-A is COMPULSORY consisting of TEN questions carrying TWO marks each.
2. SECTION-B contains FIVE questions carrying FIVE marks each and students have to attempt any FOUR questions.
3. SECTION-C contains THREE questions carrying TEN marks each and students have to attempt any TWO questions.

SECTION-A

Q1. Write briefly :

- a) Differentiate between static aeroelasticity and dynamic aeroelasticity.
- b) List the static aeroelastic problems.
- c) What is buffeting? How is it alleviated?
- d) Define 'Control system reversal'.
- e) What were the reasons for the absence of aeroelastic problems prior to World War-II?
- f) List the effects of flutter on the design of high speed aircraft.
- g) State the effect of dynamic loads on airplane design.
- h) What is the effect of sweep on divergence speed of a wing?
- i) Sketch the effect of speed on aileron effectiveness.
- j) What are the degrees of freedom of the oscillating motion of a fluttering cantilever wing?

SECTION-B

- Q2. Explain the effect of sweep on critical speeds with the help of a sweep versus speed diagram.
- Q3. Making suitable assumptions and Saint-Venant's torsion theory, derive a differential equation for the determination of divergence speed of an idealized cantilever wing.
- Q4. Derive a relation between $\frac{\partial C_L}{\partial \beta}$ and $\frac{\partial C_{mac}}{\partial \beta}$ that makes aileron reversal speed of a wing equal to its divergence speed.
- Q5. Describe the physical phenomenon of flutter.
- Q6. Explain the phenomenon of galloping of transmission lines.

SECTION-C

- Q7. Derive an expression for the aileron reversal speed of a two-dimensional wing in terms of $\frac{\partial C_L}{\partial \beta}$, $\frac{\partial C_L}{\partial \alpha}$ and $\frac{\partial C_{mac}}{\partial \beta}$ where the symbols have their usual meanings.
- Q8. State semirigid theory. Making use of suitable assumptions and semirigid assumption, derive the following equation :

$$q_{div} a \int_0^s C^2(y) e(y) \frac{f^2(y)}{f^2(r)} dy = k$$

- Q9. Write notes on :
- Effect of aeroelasticity on static longitudinal stability of airplane.
 - Method of successive approximations.

NOTE : Disclosure of Identity by writing Mobile No. or Making of passing request on any page of Answer Sheet will lead to UMC against the Student.