

<b>R09</b>
------------

**Code No: C2004****JAWAHARLAL NEHRU TECHNOLOGICAL UNIVERSITY HYDERABAD****M.Tech I - Semester Examinations, March/April-2011****ADVANCED REINFORCED CONCRETE DESIGN****(STRUCTURAL ENGINEERING)****Time: 3hours****Max. Marks: 60**

**Answer any five questions**  
**All questions carry equal marks**

- - -

- 1.a) Explain whether moment redistribution can be applied to reduce bending moments in columns.
- b) Determine the ordinates of the bending moment diagram at every one-tenth point of beam AB of span 20 m with a uniformly distributed load 35 kN/m if the fixed moments at A is 1200 kNm and that at B is 700 kNm. [6+6]
2. Using yield line theory, design the floor slab of a class room of a multi-storeyed structure for the following data. Dimensions of the class room are 6 m x 6 m. The panel is continuous on all edges. Assume M30 concrete and Fe415 grade steel. Derive the formulae involved. Sketch the reinforcement details. Assume moderate exposure condition. [12]
3. Design a 5.5m x 5.5m wide flat slab, simply supported at the periphery, by a masonry wall 230 mm thick. Assume a live load of 4kN/m<sup>2</sup> and finish load of 1 kN/m<sup>2</sup>. Use direct design method. Use M35 concrete and Fe 500 grade steel. Sketch the reinforcement details. Assume mild exposure condition. [12]
4. Design a ribbed slab 6 x 6 m continuous over two adjacent sides simply supported on the other two sides if it is beams so that beams are spaced at 1.5 x 1.5m. Assume factored udl of 12 kN/m<sup>2</sup>. Use M30 concrete and Fe415 steel. [12]
- 5.a) What do you mean by the term 'shear span'? Explain its effect on strength of RC members.
- b) Design a corbel to carry a factored load of 630 kN at a distance of 250 mm from the face of a 300 x 300 mm column. Use M35 concrete and Fe 415 grade steel. [6+6]
6. A reinforced concrete deep girder is continuous over spans of 8 m apart, from center to center. It is 4.5 m deep, 300 mm thick and the supports are columns 800 mm in width. If the girder supports a udl of 250 kN/m including its self weight, design the necessary reinforcement. Use M25 concrete and Fe 415 grade steel. [12]

**Contd...2**

::2::

7. Design a shear wall of length 6 m and thickness 275 mm subjected to the following forces (fig.1). Assume moderate exposure condition. Assume  $f_{ck} = 30 \text{ Mpa}$  and  $f_y = 415 \text{ N.mm}^2$  and the wall is a high wall with the following loadings: Sketch the reinforcement details. [12]

Loading	Axial Force (kN)	Moment (kNm)	Shear(kN)
Dead Load + Live Load	2050	650	40
Seismic Load	300	5200	650




Fig.1 Shear wall

- 8.a) Distinguish between short-term and long-term deflections in RC members.
- b) A simply supported one-way slab 180 mm having an effective span of 4.2 m is reinforced with 10 mm diameter bars spaced at 125 mm c/c at an effective cover of 25 mm. The slab is subjected to a live load of  $4 \text{ kN/m}^2$  and a surface finish of  $1.6 \text{ kN/m}^2$ . Use M25 concrete and Fe 500 grade steel. Assume ultimate shrinkage strain = 0.0003 and creep coefficient = 1.6. Estimate the only the long-term deflection. [6+6]

--ooOoo--